



**3-3.5t**  
G Series AC Electric Forklift

Standard configuration

- Wide view mast
- Standard fork
- II (II) fork carriage
- Backrest
- Two-spool control valve
- Battery group
- Standard seat
- Overhead guard
- Overhead guard raincoat
- LCD combined display
- Pneumatic tyres
- Traction bar
- Attached tools
- Flashing light

Optional

- Boom
- Cab
- Load hook
- String bar
- Hinged fork
- Back view mirror
- Side shifter
- Paper roll clamp
- warning light (rotating or buzzing)
- Solid tyre
- Rear work lights
- Protective fences
- Multi function barrel clamp
- Load stabilizer
- Widened fork carriage
- Lengthened fork
- Load pusher
- Fork sleeve
- Rotating flat clamp
- Dual-tyres protector
- Accessory hydraulic component
- Tilt/Steering cylinder protection sleeve
- Colored tyre(white/green)
- Wide view double/triple full free mast
- User-specified color



**HELI** 安徽合力股份有限公司  
ANHUI HELI CO., LTD.  
ADD: NO.688 Fangqing Street, Economical Development Zone, Hefei, P. R. China  
TEL: (86 551) 63635006, 63635258, 63635958, 63662105  
FAX: (86 551) 63635996  
WEBSITE: <http://www.helichina.net>

AUTHORIZED DEALER



**3-3.5t**  
G Series AC Electric Forklift

G series / INTELLIGENT ENVIRONMENT-FRIENDLY

**G 3-3.5t**  
G Series AC Electric Forklift

Newly designed wide-view mast



The newly designed wide-view mast effectively enlarges operators' view and lessens the blind area to provide a clearer vision.

**↑ 7%**  
THE FIRST VIEW INCREASES

Excellent steering system



The Steering system with new technologies not only provides a smoother swerve and faster positioning & steering, but also effectively lowers down the noise.

- ✓ New integrated load-sensing steering
- ✓ Power Steering
- ✓ New low-noise gear pump with differential tooth technology

AC drive motor



**↑ 50%**  
gradient performance increases

**↑ 25%**  
The maximum travel speed increases

- ✓ Large ratio gearbox
- ✓ Motor maintenance
- ✓ Maintain more efficient
- ✓ Renewable energy technologies

The wonderful combination of high-power AC motor and the new style gearbox by independent R&D fully enhance the performance of acceleration, driving and grade ability.

G series / INTELLIGENT ENVIRONMENT-FRIENDLY

High efficiency loading/unloading performance

The innovative design and configuration of hydraulic system improve the working efficiency largely and provide a very efficient loading/unloading.

**↑ 20%**  
The maximum unloaded lifting speed increases

**↑ 12%**  
The maximum loaded lifting speed increases



- ✓ New low-speed & high-torque lifting motor
- ✓ MOSFET lifting controller
- ✓ New dynamic load sensing technology in hydraulic system
- ✓ Optional AC lifting system greatly enhances the loading/unloading performance.

Enough operation space

The new optimization layout widens the operator space for ensuring more comfortable and convenient operation.

**↑ 12%**  
The operating space increases



More intelligent performance

The truck equipped with more intelligence functions not only ensures the safety performance, but also improves the efficiency and reduces energy consumption.

- ✓ Standard CAN BUS
- ✓ Self-braking on ramp
- ✓ Preventing abnormality operating
- ✓ AC traction controller
- ✓ Emergency power shut-down
- ✓ Electric controller self-protecting
- ✓ Presence of driver sensing system
- ✓ Speed selection function (normal/cutback)



ZAPI CONTROLLER




CURTIS CONTROLLER



**3-3.5t**  
G Series AC Electric Forklift

Manufacturer's Data and Design Characteristics				
Characteristics				
1.01	Manufacturer's Name	HELI		
1.02	Model Designation	CPD30	CPD35	
1.03	Configuration Number	G1432	G1152	
1.04	Load Capacity	Q kg	3000	3500
1.05	Load Center	c mm	500	500
1.06	Power Type	Battery	Battery	
1.07	Operator Type	Seated	Seated	
1.08	Wheelbase	L1 mm	1680	1680
Wheels & Tyres				
2.01	Tyre Type		Pneumatic	Superelastic
2.02	Tyres Number (Front/Rear)		2/2	2/2
2.03	Tread (centre of tyre) front	W3 mm	1000	1000
2.04	Tread (centre of tyre) rear	W2 mm	980	980
2.05	Tyre Size, Front		28-9-15-12PR	28-9-15
2.06	Tyre Size, Rear		18-7-8-14PR	18-7-8
Dimensions				
3.01	Load Distance	L2 mm	485	490
3.02	Max. Tilt Angle, F/R	α/β	6/10	6/10
3.03	Height with Mast Lowered	H1 mm	2075	2180
3.04	Free Lift	H3 mm	145	150
3.05	Standard Lift Height	H mm	3000	3000
3.06	Height with Mast Extended	H2 mm	4182	4177
3.07	Overhead Guard Height	H4 mm	2215	2215
3.08	Fork Size T×W×L	T×W×L4 mm	45×125×1070	50×125×1070
3.09	Fork Carriage to DIN 15173 A/B		3A	3A
3.10	Length to fork face	L' mm	2465	2550
3.11	Overall Width	W1 mm	1225	1225
3.12	Outside Turning Radius	r mm	2210	2270
3.13	Ground Clearance at mast, Loaded	H5 mm	135	135
3.14	Ground Clearance at centre of wheelbase, Loaded	H6 mm	150	150
3.15	Right angle stacking aisle width (Clearance: 200mm)	Ast mm	3965	4030
3.16	Right angle stacking aisle width (Clearance: 200mm)	Ast mm	4095	4160
3.17	Lateral Fork Adjustment (Outside of Forks) Max./Min.	W5 mm	1060/250	1060/250
Performances				
4.01	Travel Speed, with/without load	km/h	15.0/15.5	14.5/15.0
4.02	Lifting Speed, with/without load	mm/s	280/450	250/440
4.03	Lifting Speed, with/without load	mm/s	340/480	320/450
4.04	Lowering Speed	mm/s	500	500
4.05	Gradient performance with load	%	17	15
4.06	Max. draw bar pull with load	N	15600	17500
4.07	Acceleration time (10 metres) W/O load	s	5.0/4.7	5.2/4.9
Weight				
5.01	Total Approximate Weight (W/O battery)	kg	4810/3460	5500/4150
5.02	Axle Loading*: Unloaded, Front/Rear	kg	2320/2490	2640/2860
5.03	Axle Loading*: Loaded, Front/Rear	kg	7055/755	8145/855
Battery				
6.01	Battery Voltage/named capacity(5h)	V/Ah	80/480	80/480
6.02	battery weight	kg	1350	1350
6.03	Battery to DIN 43531/35/36/A/B/C		43536A	43536A
Motor & Controller				
7.01	Drive Motor - 60 Min. Rating	KW	16.6(AC)	16.6(AC)
7.02	Pump Motor - 15 Min. Rating	KW	13(DC)	13(DC)
7.03	Pump Motor - 15 Min. Rating	KW	13.5(AC)	13.5(AC)
7.04	Drive Motor Control Method		MOSFET/AC	MOSFET/AC
7.05	Pump Motor Control Method		MOSFET/DC	MOSFET/DC
7.06	Pump Motor Control Method		MOSFET/AC	MOSFET/AC
7.07	Service Brake/Parking Brake		Hydraulic/Mechanical	Hydraulic/Mechanical
7.08	Relief Pressure	Mpa	21	21

NOTE: \* stands for the parameters and configurations when choosing the AC type lifting system.



Note: The vertical axis stands for load capacity and the horizontal axis stands for load center which is calculated from the front surface of the forks to the gravity of the standard load. The standard load means a cubic with 1000mm edge length. When mast is tilted forward, using non-standard forks or loading large goods, the load capacity will be reduced. The load capacity of standard mast at different load center can be known from this load chart.





Renewable energy technologies

With the use of the excellent load-sensing steering system and AC controlling renewable energy technologies, the forklift is more energy-saving and the working hour of the battery is extended by 15%.

**↑ 15%**  
THE PERFORMANCE OF BATTERY INCREASES

The reliable special instrument gives a complete display of the key information, like operating status, fault detection, etc. It ensures the operator predominate the vehicle status more intuitive and convenient.



WIDE VIEW MAST						
Mast model	Max Fork height (mm)	Load Capacity (Load center 500mm) (kg)		Overall Height (mm)		Tilt Angle (1/11)
		CPD30	CPD35	CPD30	CPD35	
M200	2000	3000	3500	1565	1680	6/10
M250	2500	3000	3500	1815	1930	6/10
M300	3000	3000	3500	2075	2180	6/10
M330	3300	3000	3500	2215	2330	6/10
M350	3500	3000	3500	2215	2430	6/10
M370	3700	3000	3400	2415	2530	6/10
M400	4000	2850	3350	2615	2730	6/10
M425	4250	2850	3250	2740	2855	6/10
M450	4500	2750	3100	2865	2980	6/10
M500	5000	2400	2850	3115	3230	6/10
M550	5500	2250	2600	3415	3530	3/8
M600	6000	*2450	*2600	3665	3780	3/8
		1500	1550			3/8
		*2200	*2400			3/8

WIDE VIEW FULL FREE 2-STAGE MAST								
Mast model	Max Fork height (mm)	Load Capacity (Load center 500mm) (kg)		Overall Height (mm)		Free lift (With STD backrest) (mm)		Tilt Angle (1/11)
		CPD30	CPD35	CPD30	CPD35	CPD30	CPD35	
ZM200	2000	3000	3500	1570	1680	344	500	6/10
ZM250	2500	3000	3500	1820	1930	594	750	6/10
ZM300	3000	3000	3500	2070	2180	844	1000	6/10
ZM330	3300	3000	3500	2220	2330	994	1150	6/10
ZM350	3500	3000	3500	2220	2430	1094	1250	6/10
ZM370	3700	3000	3400	2420	2530	1194	1350	6/10
ZM400	4000	2950	3350	2620	2730	1394	1550	6/10
ZM425	4250	2850	3250	2745	2855	1519	1675	6/10
ZM450	4500	2750	3100	2870	2980	1644	1800	6/10
ZM500	5000	2400	2850	3120	3230	1894	2050	6/10
ZM550	5500	2250	2600	3420	3530	2194	2350	3/8
ZM600	6000	1500	1550	3670	3780	2444	2600	3/8
		*2200	*2400					3/8

WIDE VIEW FULL FREE 3-STAGE MAST								
Mast model	Max Fork height (mm)	Load Capacity (Load center 500mm) (kg)		Overall Height (mm)		Free lift (With STD backrest) (mm)		Tilt Angle (1/11)
		CPD30	CPD35	CPD30	CPD35	CPD30	CPD35	
ZSM300	3000	3000	3400	1946	1946	670	670	6/6
ZSM400	4000	2900	3250	2065	2065	795	795	6/6
ZSM435	4350	2750	3150	2190	2190	920	920	6/6
ZSM450	4500	2700	3000	2240	2240	970	970	6/6
ZSM470	4700	2650	2850	2240	2240	970	970	6/6
ZSM480	4800	2600	2800	2340	2340	1070	1070	6/6
ZSM500	5000	2400	2650	2440	2440	1170	1170	6/6
ZSM540	5400	2250	2500	2565	2565	1295	1295	3/8
ZSM600	6000	1500	1550	2790	2790	1520	1520	3/8
		*2150	*2300					3/8

NOTE: (1) \* Rated capacity with front dual tires;  
(2) CPD30 The free height of full free 2-stage mast without backrest increase 400mm;  
(3) CPD35 The free height of full free 2-stage mast without backrest increase 412mm;  
(4) The free lift height of full free 3-stage mast without backrest increase 520mm.